


Human Machine Interface



Unit : mm

Sub-models	20 / 40	Micro SD Slot	N/A
View Size	10.1" diagonal	USB Client	YES (USB 1.1)
Display Type	TFT LCD with LED Backlight	USB Host	YES (USB 1.1)
Max. Colors	16-bit	COM1	RS232/RS422/RS485
Backlight Life (hr)	20000	COM2	N/A
Display Luminance	150 (cd/m ²)	COM3	RS232 (optional: RS485)
Max. Resolution	1024*600	Ethernet	Sub-Model 40 : YES
Display Contrast	500	Power Connector	24VDC±10% Isolated
CPU	RISC ARM9 32Bit	Power Consumption	20W
Touch Panel	4-wire Analog Touch Panel	Operating Temp.	0°C~50°C
Backup SRAM	128KB (optional: 1MB)	Relative Humidity	10%~90%
Working Memory	32MB	Shock (Operation)	10 ~ 55Hz(X,Y,Z direction, 1G, 30 Mins shock testing)
Built-in Storage Memory	8MB+128MB (NAND Flash)	EMI	FCC Part 15 Class A
Real-Time Clock (RTC)	YES	CE	EN61000-6-2, EN61000-6-4
Front Function Keys	N/A	UL Certification	N/A
Audio out (optional)	N/A	Ingress Protection	IP65
Video in (optional)	N/A	Cooling	Natural Cooling
Front USB Host Port	N/A	Dimensions (WxHxD)Unit : mm	270.1 x 212.1 x 42.5
Net Weight (kg)	1.1	Cutout Dimensions (WxH)Unit : mm	259.5 x 201.5

Contact

Head Office

Add: 11F., No.168, Jiankang Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)

Tel: +886-2-2228-7950 (Rep.)

Fax: +886-2-2228-6140

E-mail : service@maxthermo.com.tw

Web : www.maxthermo.com

Showroom

Add: 3C25, Taipei World Trade Center, No. 5, Sec. 5, Hsin Yi Rd. Taipei Taiwan, R.O.C.

Tel: +886-2-2720-6601

Fax: +886-2-2345-5120

Thailand Office

Add: 86/132-133 m.7 Samaedum Bangkoontien 10150 Thailand.

Tel: +662-415-8318 , +662-417-2548-49

Fax: +662-415-8798

Web : www.thaimaximum.com